


# Y-TYPE™

## Polyurethane and Carbide Secondary Cleaner

### Simple. Affordable. Effective.

The Y-Type™ Secondary Belt Cleaner improves belt cleaning efficiency and reduces routine maintenance tasks. With an easy, do-it-yourself installation and simple, serviceable blades, all at an affordable price, it makes for an ideal solution for your belt cleaning needs.



### Features and Benefits

- Belt speeds up to 3M/s (600 fpm) for standard duty, up to 3.8M/s (750 fpm) for heavy duty.
- Works on reversing belts.
- Available in 450 - 1200mm (18" - 48") for standard duty belts, 900 - 1800mm (36" - 72") for heavy duty belts.
- 75mm (3") wide blade segments. Conforms to worn or damaged belts.
- Blades available in carbide and purple or white/food grade polyurethane.
- **Easy maintenance.** Simple design makes changing the blades fast and easy. Blades can be removed and replaced individually, or all at once by replacing the cartridge.
- **Spring tensioner.** Utilizes the YST tensioner to maintain constant pressure on the belt. Standard duty YST for 60mm (2-3/8") poles, heavy duty YST for 73mm (2-7/8") poles.
- **White food-grade blade** is chemical resistant, and all ingredients used in polyurethane formulation comply with the relevant requirements of 21 CFR (FDA Code of Federal Regulations) for use in repeated bulk dry food applications.

# Y-Type™ Polyurethane and Carbide Secondary Cleaner

## Specifications and Guidelines

	Standard Duty	Heavy Duty
Maximum Belt Speed	3 M/sec (600 FPM)	3.8 M/sec (750 FPM)
Temperature Rating	-35° C to 82° C (-30° F to 180° F)	
Usable Blade Wear Length	Polyurethane: 50 mm (2")	Polyurethane: 75 mm (3")
	Carbide: 6 mm (1/4")	Carbide: 10 mm (3/8")
Available for Belt Widths	450 to 1200 mm (18" to 48")	900 to 1800 mm (36" to 72")


### Blade Material

Purple: Polyurethane (proprietary blend for abrasion resistance and long wear)

White: Polyurethane (chemical resistant/food grade)\*

Carbide: Impact resistant tungsten carbide

\*All ingredients used in polyurethane formulation comply with the relevant requirements of 21 CFR (FDA Code of Federal Regulations) for use in repeated bulk dry food applications.



**Horizontal Clearance Required**  
**Standard Duty:** 110 mm (4-1/4")  
**Heavy Duty:** 135 mm (5-1/4")

**Vertical Clearance Required**  
**Standard Duty:**  
 Polyurethane: 210 mm (8-1/4")  
 Carbide: 185mm (7-3/4")  
**Heavy Duty:**  
 Polyurethane: 240 mm (9-1/2")  
 Carbide: 250 mm (9-3/4")

### Pole Length

SD Belt width + 762 mm (30")  
 HD Belt width + 1372 mm (54")

### Maximum Conveyor Span

SD Belt width + 559 mm (22")  
 HD Belt width + 1169 mm (46")

## Ordering Information

Y-Type Secondary Cleaners - Standard Duty							
Belt Width		Carbide Blades		Purple Polyurethane Blades		White/Food Grade Polyurethane Blades	
mm	in.	Ordering Number	Item Code	Ordering Number	Item Code	Ordering Number	Item Code
450	18	YT-TC-18S	79759	YT-18S	79765	YTW-18S	79771
600	24	YT-TC-24S	79760	YT-24S	79766	YTW-24S	79772
750	30	YT-TC-30S	79761	YT-30S	79767	YTW-30S	79773
900	36	YT-TC-36S	79762	YT-36S	79768	YTW-36S	79774
1050	42	YT-TC-42S	79763	YT-42S	79769	YTW-42S	79775
1200	48	YT-TC-48S	79764	YT-48S	79770	YTW-48S	79776


Lead time: 1 working day

Y-Type Secondary Cleaners - Heavy Duty							
Belt Width		Carbide Blades		Purple Polyurethane Blades		White/Food Grade Polyurethane Blades	
mm	in.	Ordering Number	Item Code	Ordering Number	Item Code	Ordering Number	Item Code
900	36	YTHD-TC-36S	79777	YTHD-36S	79783	YTHDW-36S	79789
1050	42	YTHD-TC-42S	79778	YTHD-42S	79784	YTHDW-42S	79790
1200	48	YTHD-TC-48S	79779	YTHD-48S	79785	YTHDW-48S	79791
1350	52	YTHD-TC-54S	79780	YTHD-54S	79786	YTHDW-54S	79792
1500	60	YTHD-TC-60S	79781	YTHD-60S	79787	YTHDW-60S	79793
1800	72	YTHD-TC-72S	79782	YTHD-72S	79788	YTHDW-72S	79794

Lead time: 1 working day

Blades Required per Cleaner Size - Standard						
mm	450	600	750	900	1050	1200
in.	18	24	30	36	42	48
Blades Required	6	8	10	12	14	16

Blades Required per Cleaner Size - HD						
mm	900	1050	1200	1350	1500	1800
in.	36	42	48	54	60	72
Blades Required	12	14	16	18	20	24



Av. Jorge Alessandri 11.500 – Edificio 7 • Megacentro San Bernardo  
 San Bernardo • Santiago, Chile  
 Teléfono: 56-2-2896-7870 • Correo electrónico: ventaslatam@flexco.com

Visite [www.flexco.com](http://www.flexco.com) para conocer otras ubicaciones y productos de Flexco.

©2017 Flexible Steel Lacing Company. 01/04/17. Para hacer otro pedido: X4203

Authorized Distributor:

